

**Pressure Vacuum Breakers**


- Pressure vacuum breaker consisting of an approved check valve, vacuum relief, inlet and outlet full port resilient seated shut-off valves and two full port resilient seated ball valve test cocks.
- Maximum operating pressure 150 psi
- Temperature range, 33 ° F-110°F



Product	Description	Pkg	Each
720A-3/4BV	¾" PVB	1	
720A-1BV	1" PVB	1	
720A-11/2BV	1½" PVB	1	

**Wilkins 350 Series**

- Smaller, shorter unit
- Top access to test cocks, ball valves, and check assembly
- Can easily be removed for winterizing, cleaning and repair
- Winterize easily thru flush/winterization insert



*Wilkins 350 and 375 winterization/flush*

**Wilkins 375 Series**

- Smaller, shorter unit
- Top access to test cocks, ball valves, and check assembly
- Check assembly can easily be removed for winterizing, cleaning and repair
- Winterize easily thru flush/winterization insert



*Wilkins 375 RPZ backflow preventer with removable pressure*


**350/375 Series Winterization/Flush Valve**

- Replaces check assembly
- Creates a convenient blow-out point
- Great for system flushing

Product	Description	Pkg	Each
3/4"-375-BOF	3/4" plastic flush/winter valve	1	
3/4" - 375- BOF	3/4" plastic flush/winter valve	1	

**Backflow Enclosures**

- Vandal & weather resistant
- Marine grade aluminum alloy



Product	Description	Pkg	Each
SB-18SS	18x36x12 SS Enclosure	1	
SBBC-45AL	45x28.5x16 Enclosure	1	
SBBC-60AL	60x28.5x16 Enclosure	1	
SBBC-60ALHP	High Profile 60x39x24 encl	1	
SBBC-90ALHP	High Profile 90x39x24 encl	1	
PED-18SS	SS Pedestal	1	



Product	Description	Pkg	Each
HB1	Enclosure, 27x13x23 (heated)	1	
HB1.5	Enclosure, 33x21x24 (heated)	1	
HB2	Enclosure, 39x13x28 (heated)	1	
lb1	Enclosure, 27x13x23	1	
lb1.5	Enclosure, 33x21x24	1	
lb2	Enclosure, 39x13x28	1	



**Double Check Assemblies**

- Double check valve assembly consisting of two independently operated spring-loaded "Y" type center guided check valves



Product	Description	Pkg	Each
950XLT-3/4	¾" DCA w/Ball Valve, w/Top Test Cock	1	
950XLT-1	1" DCA w/Ball Valve, w/ Top Test Cock	1	
950XL-11/4	1¼" DCA w/ Ball Valve	1	
950XL-2	2" DCA w/Ball Valve	1	
350-3/4	¾" DCA	1	
350-1	1" DCA	1	

**Reduced Pressure Principle (RPZ)**

- Reduced pressure principle backflow preventer consists of a pressure differential relief valve located between two independently operated spring-loaded center guided check valves.



Product	Description	Pkg	Each
975XL-3/4	¾" RPZ w/Ball Valve	1	
975XLV-3/4	¾" RPZ w/Ball Valve in/out unions swivel	1	
975XL-1	1" RPZ w/Ball Valve	1	
975XL-11/2	1½" RPZ w/ Ball Valve	1	
975XL-2	2" RPZ w/Ball Valve	1	
975XLU-3/4	¾" RPZ w/unions	1	
975XLU-1	1" RPZ w/unions	1	
375-1	1" RPZ	1	
375- 3/4	¾" RPZ	1	

**Dual Check Assembly**

- Includes two in-line poppet type
- All bronze construction
- Corrosion resistant internal parts
- May be installed vertically or horizontal
- Maximum pressure: 175PSI
- Maximum temperature: 18 degree F
- Cartridge check modules



Product	Description	Pkg	Each
705-3/4	¾" FIPT x FIPT plastic	1	
760F-3/4	¾" FIPT x FIPT w/ ATM Drain	1	
705-1	1" FIPT x FIPT plastic	1	
700F-1	1" FIPTXFIPT Dual Check, Bronze	1	
700F	FIPT X FIPT. Bronze	1	

**Backflow Accessories**

- Air Gaps**
- For use with 1/4" through 10" backflow preventers on horizontal installations.
- Can be easily mounted to body.
- An air gap is necessary when installing a drain line.



Product	Description	Pkg	Each
<b>Wilkins</b>			
AG-2	Air Gap, 575 1 1/4" -2"	1	
AG-4	Air Gap, 975 3/4"-1"	1	
AG-5	Air Gap, 975 1 1/4"- 2"	1	

Product	Description	Pkg	Each
3/4"-375-BOF	¾" plastic flush/winter valve	1	